



Certificate of Compliance

This certificate is issued for the following:

Wooden and wood/gypsum/metal construction safety cabinets per FM Standard 6050

Prepared for:

asecos GmbH Sicherheit und Umweltschutz
Weiherfeldsiedlung 16-18
Gründau, D-63584
Germany

FM Approvals Class: 6050

Approval Identification: 3053853

Approval Granted: 6/26/2015

To verify the availability of the Approved product, please refer to www.approvalguide.com

Said Approval is subject to satisfactory field performance, continuing Surveillance Audits, and strict conformity to the constructions as shown in the Approval Guide, an online resource of FM Approvals.

A handwritten signature in dark ink that reads 'Cynthia E Frank'.

Cynthia Frank
AVP - Manager of Materials
FM Approvals
1151 Boston-Providence Turnpike
Norwood, MA 02062



Member of the FM Global Group

Storage Cabinets for Flammable and Combustible Liquids

These cabinets are for the storage of flammable liquids in containers not exceeding 55 gallon (210 L) capacity. Total cabinet capacity is limited to 120 gallon (455 L); max storage of liquids in drums is limited to vertical orientation of drums to preclude self-dispensing. Cabinets are constructed of at least 18 gauge steel with a 1 1/2 in. (38 mm) air space all around between the inner and outer surfaces including door openings, or from at least 1 in. (25 mm) plywood. Doors have a lockable 3 point latching system and the door sill is at least 2 in. (51 mm) above bottom of cabinet. The cabinets are equipped with a 2 in. (51 mm) deep, leak-tight, sump or pan. Each cabinet has also passed a 10 minute exposure fire test according to a time-temperature relationship described in ASTM E152 in which internal temperature (at top center) cannot exceed 325°F (163°C).

Q90.195.120, Q90.195.090, Q90.195.060, Q30.195.116, Q30.195.086.WD, Q30.195.056

Product Number	Size W x D x H (in)	Capacity-Gal. (L)	Door style
Q90.195.120	1193 x 615 x 1953 (47 x 24 x 77)	75 gal. (284 L)	Self closing dual door, in the event of a fire
Q90.195.090	893 x 615 x 1953 (35 x 24 x 77)	50 gal. (189 L)	Self closing dual door, in the event of a fire
Q90.195.060	599 x 615 x 1953 (23-1/2 x 24 x 77)	25 gal. (95 L)	Self closing single door, in the event of a fire
Q30.195.116	1164 x 620 x 1947 (46 X 24-1/2 X 76-1/2)	75 gal. (284 L)	Self closing dual door, in the event of a fire
Q30.195.086.WD	864 x 620 x 1947 (34 X 24-1/2 X 76-1/2)	50 gal. (189 L)	Self closing single door, in the event of a fire
Q30.195.056	564 x 620 x 1947 (22 X 24-1/2 X 76-1/2)	25 gal. (95 L)	Self closing single door, in the event of a fire

Company Name:	asecos GmbH Sicherheit und Umweltschutz
Company Address:	Weierfeldsiedlung 16-18, Gründau D-63584, Germany
Company Website:	http://www.asecos.com
New/Updated Product Listing:	No
Listing Country:	Germany
Capacity (Gallons):	25, 50, 75
Capacity (Liters):	95, 189, 284
Certification Type:	FM Approved